



# THREE PHASE EPS BOX PRO



Max. input current  
(per phase) 63A



Safety



IP65 Rated



Quickly Installation

- Max. input current (per phase) 63A
- PC+ABS ,Robust plastic enclosure IP65
- Easy installation, plug and play
- Applied to residential, commercial solar installations
- Compatible with H3/AIO H3 series
- Automatically switch to Off-Grid state



## SPECIFICATIONS

| MODEL                                  | EPS BOX PRO                       |
|--|-----------------------------------|
| <b>UTILITY SUPPLY</b>                  |                                   |
| Rated Voltage [VAC]                    | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                   | 50 / 60                           |
| Max. Input Current (Per Phase) [A]     | 63                                |
| <b>INVERTER GRID</b>                   |                                   |
| Rated Voltage [VAC]                    | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                   | 50 / 60                           |
| Max. Input Current (Per Phase) [A]     | 25                                |
| <b>INVERTER EPS</b>                    |                                   |
| Rated Voltage [VAC]                    | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                   | 50 / 60                           |
| Max. Input Current (Per Phase) [A]     | 25                                |
| <b>Load</b>                            |                                   |
| Rated Voltage [VAC]                    | 220 / 380, 230 / 400, 3L / N / PE |
| Rated Frequency [Hz]                   | 50 / 60                           |
| Max. Output Current (Per Phase) [A]    | 63                                |
| <b>Communication Interface</b>         |                                   |
| RS-485 (Meter)                         |                                   |
| <b>General Data</b>                    |                                   |
| Cooling Concept                        | Natural                           |
| Installation                           | Wall-mounted                      |
| Operating Temperature Range [°C]       | -25 ~ +60 (Derating at 45)        |
| Dimensions (W * H * D) [mm]            | 550 * 420 * 138.5                 |
| Dimensions of packing (W * H * D) [mm] | 660 * 515 * 235                   |
| Net Weight [kg]                        | 16                                |
| Gross Weight [kg]                      | 19.3                              |
| Ingress Protection                     | IP65                              |

